

# Webblon® Coast Line PLUS®

2015-2016

62" wide / 15 oz. per square yard (weight varies slightly from color to color)

Coastline Plus® awning fabric is a high performance PVC composite that features a strong polyester base fabric. The top surface is treated with the Rain Kleen® finish for color retention and prolonged fabric life. Coastline Plus® is UV, water, and mildew resistant, and is backed by a 5-year limited warranty.


Coastline Plus is available in solids, complement solids, linen-backed solids and select stripe patterns. It is extra strong, with manageable weight for superior resistance to sag and stretch.

Flame resistance meets or exceeds the standards of California State Fire Marshal, NFPA -701 TM2, and ASTM E-84 Class A flame spread.



## Coastline Plus® Duplex Patterns

Solid topside with Linen print underside.



Colors are representative only. Small variations in shade should be anticipated and are within commercial tolerances.





## Care and Cleaning Awning Fabric

Coastline Plus™ Awning Fabric is a polyester reinforced PVC fabric that will provide many years of satisfactory service. It is waterproof, flame, mildew, stain and dirt resistant. Herculite's Rain Kleen® surface treatments further enhance longevity and ease of maintenance. Coastline Plus™ is dimensionally stable. Properly fastened to the frame, it will retain its trim fit as well as its protective function and aesthetic value. Since no material is impervious to all hazards, proper maintenance is important if maximum life of the product is to be realized. The following maintenance suggestions are offered:

1. Keep clean. Occasional hosing with clear water will prevent dirt accumulation. Most dirt accumulation can be removed by mild soap, water and a soft scrub brush. Rinse thoroughly. In extreme cases, most dirt can be removed by applying half strength bleach and brushing softly to cover thoroughly the necessary area. Allow solution to remain for two or three minutes, then thoroughly rinse with clear water, protecting surrounding materials or plant growth that might be damaged by the bleach.
2. In areas particularly conducive to mildew, brush away any visible accumulation of dirt on underside. Mildew can grow on dirt, but does not grow on or attack the Coastline Plus™ vinyl.
3. Use care during installation, take down and transporting. Frictional heat, particularly at the folds, can damage the surface. Sufficient frictional heat can create holes.
4. Avoid excessive wind whip or flapping. Normally fastened sections or panels should be rolled or restrained when not in use.



HERCULITE®

P.O. Box 435, Emigsville, PA 17318 USA

717-764-1192

800-772-0036

Fax: 717-764-5211

[www.herculite.com](http://www.herculite.com)

EMAIL: [customercare@herculite.com](mailto:customercare@herculite.com)



## Specifications

Description:	Vinyl laminated on a weft insertion scrim base of high tenacity filament polyester.
Weight:	15 oz. per lineal yard
Width:	62 inches / 157.48 centimeters
Surface:	Top surface treated with Rain Kleen® for color retention and prolonged fabric life.
Transparency:	Some light color shades offer good illumination.
Abrasion Resistance:	Excellent
Dimensional Stability:	Excellent
Flexibility:	Excellent in both hot and cold environments
Flame Resistance:	Meets California State Fire Marshall Title 19, NFPA-701 ASTM E84-81A Flame Spread Rating Class A (15)
Mildew Resistance:	Excellent
Chemical Resistance:	Excellent
Water Repellency:	Excellent – Water Proof
Oil Resistance:	Excellent
Sewability:	Excellent
Heat Sealability:	Excellent. Can be sealed by hot air weg welder or radio frequency bar type.



HERCULITE®

P.O. Box 435, Emigsville, PA 17318 USA

717-764-1192

800-772-0036

Fax: 717-764-5211

[www.herculite.com](http://www.herculite.com)

EMAIL: [customercare@herculite.com](mailto:customercare@herculite.com)



## Coastline Plus™ Limited Warranty

Coastline Plus™ Awning Fabrics are guaranteed for a period of five (5) years from date of original installation against rot or excessive deterioration, mildew stains, excessive loss of strength or color change if they occur in normal use and exposure, including sunlight and normal atmospheric chemicals. (Some color change is unavoidable due to ultraviolet rays and chemicals in the atmosphere.)

In the unlikely event of failure of fabric during the five (5) year period from date of original installation, we will supply you, the original owner or the provider of your protective fabric accessories with replacement fabric at no charge.

This warranty protects you against damage to the fabric accessories used under normal conditions. It does not cover damage to the fabric from acts of God, vandalism, neglect or improper use.

**This warranty is in lieu of all warranties expressed or implied, and, Herculite Products Inc. will not be liable for any consequential or incidental damage. Any implied warranties imposed by law are limited in time to the duration of the expressed warranty.**

Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damage, so, the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.



HERCULITE®

P.O. Box 435, Emigsville, PA 17318 USA

717-764-1192

800-772-0036

Fax: 717-764-5211

[www.herculite.com](http://www.herculite.com)

EMAIL: [customer care@herculite.com](mailto:customer care@herculite.com)